

Catalogue & Price List



## **LIGHT**

## IP65-IP67

## Watertight junction boxes

The Light series is a set of watertight surface boxes intended for electrical junctions or for trunking boxes.

They can also be used to build electrical or electronic switchboards. With the right accessories, small terminal junction boxes can be built, and power sockets can be used to create small electric power supply blocks.

This series is completed with the motor-protection and electrical and electronic protection boxes for machine tools or similar applications.



#### LIGHT Technical Specifications

- Degree of protection: IP65-IP67\*.
- Resistance to impact: IK07.
- Glow wire resistance: 650  $^{\circ}\text{C}.$
- Ball pressure test: 70 °C.
- Ambient temperature range: -25 °C / +40 °C.
- Maximum operating voltage: 1000 V AC/1500 V DC.
- Double insulation: Class II.
- \* Except ref. EP048, EP088 and EX088 (IP54).

#### **LIGHT Certifications**

Compliant with the Low Voltage Directive 2014/35/EU. Standards: IEC 60998-2-5 and IEC 60670-24.

## LIGHT

#### IP65-IP67 junction boxes



#### Supply

- The boxes are supplied individually, shrink-wrapped and in multiple cardboard packaging, according to minimum packaging units.
- EP048 is not supplied shrink-wrapped, it is supplied with the label over the cover.
- Boxes with conical cable glands are supplied with the cone assembled.
- Accessory bag: Bag with 2 arrow screws plus 2 screws without arrow.

#### **Product series**

#### Standard:

- Seven watertight junction boxes.
- Three watertight motor-protection boxes.
- Each of these models is manufactured in three different versions:

With conical cable glands.

With knock-out sides.

With plain sides.

- The three largest models are available with opaque or transparent cover.

A series of assemblies with standard power sockets is offered.

#### Special:

- Using the basic versions, special versions can be created to suit the needs of each customer or to comply with the specific regulations of the target markets.
- Special assemblies with power sockets can be supplied in any combination, with no minimum order quantity.

#### Material

- Halogen-free plastic materials.
- Opaque base and cover: Shock-proof PS RAL 7035.
- Transparent cover: PC tinted window, with UV protection.

# Possibility of special assemblies with no minimum order quantity

#### Table for DIN rails

Box type	Direction	Hole distance	Rail length	Rail code
		(mm)	(mm)	
65DS111	Vertical Horizontal	77.5 77.5	90 90	92711
65DS161	Vertical Horizontal	77.5 127	90 137	92711 92713
65DS/GS171	Vertical Horizontal	127 127	137 137	92713
65DS/GS231	Vertical Horizontal	139 187	166 214	92721 92722
65DS/GS322	Vertical Horizontal	187 312	214 325	92722











#### Base

- The junction and motor-protection boxes are available in three versions:
  - Plain sides.
  - Sides with closed knock-outs, adapted to the metric and easy to remove.
  - Sides with cut-outs for fitting conical cable glands.
- The wall-mounting points are located at the bottom of the base and can be hermetically isolated using caps that guarantee the box's IP protection and dielectric strength. These caps are supplied as an accessory (Ref. 77650).
- There are also slotted ribs at the bottom of the base for securing tap-off terminals and plates.
- The supports for securing the DIN rails are also located there. They can be ordered as an accessory (see page 248).
- There are closed knock-outs on the outside of the box bottom to facilitate the entry of cables from the back.
- There are vertical ribs on the four inside walls to give the part greater rigidity.
- There are also open or closed cut-outs, depending on the versions. These cut-outs have a diameter of 25 or 40 mm and the number and size depends on the box size.

#### Covers

- The covers are smooth and rounded and, together with the inside ribs, afford the whole unit excellent rigidity.
- In the 111 to 322 models, the covers have a continuous recess for an injected rubber gasket that guarantees maximum IP65-IP67 protection. These covers have a clip to make the screws captive.
- The EP048 and EP088 models have a base-cover clipping system that delivers IP54 protection.
- The covers used for motor-protection boxes are higher to be able to house the electrical devices typical of this type of box.

#### **Screws**

- These boxes are supplied with four ¼ turn plastic screws made captive by means of a clip located on the cover. The covers of the references EP048 and EP088 are clipped without screws.
- Two of the screws have pins that give the cover a hinge effect and keep the unit together.
- These screws have a hole through them, and once in place they face a hole in the cover, making it possible to seal the box and prevent access to the inside.







#### Conical cable glands

- The conical cable glands have diameters of 25 mm and 40 mm.
- They are supplied in the EP\*\*\* and EV\*\*\* versions and are always assembled in the box.
- The cones are manufactured with a flexible material that guarantees a suitable degree of protection in all cases.
- The design of the cones consists of rings placed at different heights. Each one of these rings corresponds to a pipe diameter for electrical installations, so that if they are cut to different heights the pipe can be inserted into the box through the conical cable gland, maintaining a perfect fit and guaranteeing watertightness.

#### Hinges

- Option to fit hinges between the cover and the base for all models of boxes and motor housings.
- The hinges come with markings showing the position of the screws for their attachment.

#### Ø of rings depending on cone model

		-			
Cones	Size 1	Size 2	Size 3	Size 4	Size 5
M25	-	-	20 mm	16 mm	$20 \text{ mm}^2$
M40	32 mm	25 mm	-	16 mm	$20 \text{ mm}^2$

## LIGHT

#### IP65-IP67 junction boxes

#### Boxes with opaque cover

Ref. No.	Dimensions	Description		entry al glands	Weight		ower diss mperatui	•	-		RATE PER / NO
HEIG	HT X WIDTH X DE	PTH	M25	M40	KG	20	25	30	35	40	
EP048	Ø84x50	With conical cable glands	4	-	0.07	1.6	2.0	2.4	2.9	3.3	450
EP088	84x84x50	With conical cable glands	7	-	0.08	1.6	2.0	2.4	2.9	3.3	550
EV111	108x108x64	With conical cable glands	7	-	0.16	2.7	3.4	4.0	4.7	5.4	750
EV161	116x162x76	With conical cable glands	6	4	0.25	3.8	4.7	5.7	6.6	7.6	1200
EV171	151x175x95	With conical cable glands	6	4	0.38	6.0	7.5	9.0	10.5	12.1	1350
EV231	180x241x95	With conical cable glands	4	6	0.53	8.6	10.8	13.0	15.1	17.3	1550
EV322	239x328x129	With conical cable glands	-	12	1.17	15.7	19.6	23.6	27.5	31.4	2250
EX088	84x84x50	Knock-out entries	7	-	0.06	1.6	2.0	2.4	2.9	3.3	450
EX111	108x108x64	Knock-out entries	7	-	0.14	2.7	3.4	4.0	4.7	5.4	650
EX161	116x162x76	Knock-out entries	6	4	0.21	3.8	4.7	5.7	6.6	7.6	1050
EX171	151x175x95	Knock-out entries	6	4	0.32	6.0	7.5	9.0	10.5	12.1	1200
EX231	180x241x95	Knock-out entries	4	6	0.46	8.6	10.8	13.0	15.1	17.3	1350
EX322	239x328x129	Knock-out entries	-	12	1.06	15.7	19.6	23.6	27.5	31.4	2100
EL111	108x108x64	Plain sides	-	-	0.14	2.7	3.4	4.0	4.7	5.4	650
EL161	116x162x76	Plain sides	-	-	0.22	3.8	4.7	5.7	6.6	7.6	1050
EL171	151x175x95	Plain sides	-	-	0.38	6.0	7.5	9.0	10.5	12.1	1200
EL231	180x241x95	Plain sides	-	-	0.47	8.6	10.8	13.0	15.1	17.3	1350
EL322	239x328x129	Plain sides	-	-	1.06	15.7	19.6	23.6	27.5	31.4	2100

#### HALOGEN-FREE PLASTIC MATERIALS

Base and opaque cover: PS RAL 7035 - Cones: RAL 7035.

Surface boxes.

References EP048-EP088-EX088: IP54.

References EV: IP65.

References EX-EL: IP65-IP67.











**EP048** 


**EP/EX088** 


EV/EX/EL111

EV/EX/EL161









<sup>\*</sup> Calculations obtained according to the CEI 890:1997 standard (including Corrigendum 1998). Method of temperature-rise assessment by extrapolation for partially type-tested assemblies (PTTA) of low-voltage switchgear and control gear.

#### **Boxes with transparent cover**

Ref. No.	Dimensions	Description		entry cal glands	Weight			sipation a re increas			RATE PER / NO
HEIG	HT X WIDTH X DE	M25	M40	KG	20	25	30	35	40		
EVT171	151x175x95	With conical cable glands	6	4	0.38	6.0	7.5	9.0	10.5	12.1	1700
EVT231	180x241x95	With conical cable glands	4	6	0.53	8.6	10.8	13.0	15.1	17.3	1900
EVT322	239x328x129	With conical cable glands	-	12	1.17	15.7	19.6	23.6	27.5	31.4	2400
EXT171	151x175x95	Knock-out entries	6	4	0.32	6.0	7.5	9.0	10.5	12.1	1550
<b>EXT231</b>	180x241x95	Knock-out entries	4	6	0.46	8.6	10.8	13.0	15.1	17.3	1700
<b>EXT322</b>	239x328x129	Knock-out entries	-	12	1.06	15.7	19.6	23.6	27.5	31.4	2600
ELT171	151x175x95	Plain sides	-	-	0.38	6.0	7.5	9.0	10.5	12.1	1550
<b>ELT231</b>	180x241x95	Plain sides	-	-	0.47	8.6	10.8	13.0	15.1	17.3	1700
ELT322	239x328x129	Plain sides	-	-	1.06	15.7	19.6	23.6	27.5	31.4	2600

#### HALOGEN-FREE PLASTIC MATERIALS

Opaque base: PS RAL 7035 - Transparent cover: PC, tinted, with UV protection - Cones: RAL 7035.

Surface boxes.

References EVT: IP65.

References EXT-ELT: IP65-IP67.




EV/EX/EL171 EVT/EXT/ELT/171





EV/EX/EL231 EVT/EXT/ELT231



EV/EX/EL322 EVT/EXT/ELT322







<sup>\*</sup> Calculations obtained according to the CEI 890:1997 standard (including Corrigendum 1998). Method of temperature-rise assessment by extrapolation for partially type-tested assemblies (PTTA) of low-voltage switchgear and control gear.



#### IP65-IP67 junction boxes

#### Motor-protection boxes with opaque cover

Ref. No.	Dimensions	Description		Cable entry o. conical glands					ccording se °C P(W		RATE PER / NO
HEIG	HT X WIDTH X DE	PTH	M25	M40	KG	20	25	30	35	40	
GSV171	151x175x155	With conical cable glands	6	4	0.49	8.2	10.2	12.3	14.3	16.4	1900
GSV231	180x241x175	With conical cable glands	4	6	0.80	12.4	15.4	18.5	21.6	24.7	2300
GSV322	239x328x188	With conical cable glands	-	12	1.61	19.4	24.2	29.1	33.9	38.8	3000
GSX171	151x175x155	Knock-out entries	6	4	0.43	8.2	10.2	12.3	14.3	16.4	1900
GSX231	180x241x175	Knock-out entries	4	6	0.77	12.4	15.4	18.5	21.6	24.7	2300
GSX322	239x328x188	Knock-out entries	-	12	1.48	19.4	24.2	29.1	33.9	38.8	3000
GSL171	151x175x155	Plain sides	-	-	0.43	8.2	10.2	12.3	14.3	16.4	1900
GSL231	180x241x175	Plain sides	-	-	0.74	12.4	15.4	18.5	21.6	24.7	2300
GSL322	239x328x188	Plain sides	-	-	1.48	19.4	24.2	29.1	33.9	38.8	3000

#### HALOGEN-FREE PLASTIC MATERIALS


Base and opaque cover: PS RAL 7035 - Cones: RAL 7035.


Transparent cover: PC, tinted, with UV protection.


Surface boxes - High cover. References GSV: IP65.

References GSX-GSL: IP65-IP67.









<sup>\*</sup> Calculations obtained according to the CEI 890:1997 standard (including Corrigendum 1998). Method of temperature-rise assessment by extrapolation for partially type-tested assemblies (PTTA) of low-voltage switchgear and control gear.



#### Motor-protection boxes with transparent cover

Ref. No.	Dimensions	Description		e entry cal glands	Weight		Power dissipation according to temperature increase °C P(W)*					
HEIG	HT X WIDTH X DE	M25	M40	KG	20	25	30	35	40			
GSVT171	151x175x155	With conical cable glands	6	4	0.53	8.2	10.2	12.3	14.3	16.4	2100	
GSVT231	180x241x175	With conical cable glands	4	6	0.87	12.4	15.4	18.5	21.6	24.7	2450	
GSVT322	239x328x188	With conical cable glands	-	12	1.61	19.4	24.2	29.1	33.9	38.8	3300	
GSXT171	151x175x155	Knock-out entries	6	4	0.46	8.2	10.2	12.3	14.3	16.4	1950	
GSXT231	180x241x175	Knock-out entries	4	6	0.80	12.4	15.4	18.5	21.6	24.7	2350	
GSXT322	239x328x188	Knock-out entries	-	12	1.48	19.4	24.2	29.1	33.9	38.8	3300	
GSLT171	151x175x155	Plain sides	-	-	0.46	8.2	10.2	12.3	14.3	16.4	1950	
GSLT231	180x241x175	Plain sides	-	-	0.80	12.4	15.4	18.5	21.6	24.7	2350	
GSLT322	239x328x188	Plain sides	-	-	1.55	19.4	24.2	29.1	33.9	38.8	3300	

#### HALOGEN-FREE PLASTIC MATERIALS

Base and opaque cover: PS RAL 7035 - Cones: RAL 7035.


Transparent cover: PC, tinted, with UV protection.

Surface boxes - High cover. References GSVT: IP65.


References GSXT-GSLT: IP65-IP67.








GSVT/GSXT/GSLT322





<sup>\*</sup> Calculations obtained according to the CEI 890:1997 standard (including Corrigendum 1998). Method of temperature-rise assessment by extrapolation for partially type-tested assemblies (PTTA) of low-voltage switchgear and control gear.

## **ECOLOGY**

## IP65 Surface distribution boxes

The IP65 watertight distribution enclosures are manufactured with the highest-quality halogen-free plastic materials and are available in ABS and Polycarbonate. They have ample space for wiring and a modular capacity from 4 to 54 modules. They are intended for indoor and outdoor use, where enclosures with a high degree of protection and design are required.

The design allows installation together with STAR socket boxes to create large distribution and supply boards. For both indoor and outdoor use, provided the components meet the required standards.







#### **ECOLOGY Technical Specifications**

Degree of protection: IP65.Resistance to impact: IK08.

- Glow wire resistance:

ABS: 650 °C.

Polycarbonate: 750 °C.

- Ambient temperature range: -25 °C / +40 °C. - Maximum operating voltage: 1000 V AC/1500 V DC.

- Double insulation: Class II.

#### **ECOLOGY Certifications**

Compliant with the Low Voltage Directive 2014/35/UE. Standards: UNE-EN 62208 and UNE-EN 61439-1 (as applicable).

## **ECOLOGY**

#### IP65 distribution boxes



#### **Product series**

- Surface enclosures with a capacity of 4, 6, 8, 12, 18, 24, 36 and 54 modules with transparent window.

#### Material

#### ABS version

- Halogen-free plastic materials, with UV protection.
- Base and frame: ABS RAL 7035 grey.
- Transparent window: PC tinted window.

#### Polycarbonate version

- Halogen-free plastic materials, with UV protection.
- Base and frame: PC RAL 7035 grey.
- Transparent window: PC tinted window. Recommended for outdoor use.

#### Supply

- Supplied in individual packaging. When several items are sent together, they are bundled together with transparent film.
- TH35x7.5 symmetrical rail in enclosures with one row of modules and a compact frame in enclosures with two or more rows of modules. They are supplied assembled in all references.
- Accessory bag:
  - Hermetic caps.
  - Cover-base locking screws.
  - Grey module cover (6 modules).
  - Module identification strips.
  - Assembly instructions.

Available in ABS and Polycarbonate UV-ray resistant with a transparent window















#### Base

- Base with double height DIN rail (from 12 modules) providing greater space on the inside for wiring and devices, and a reinforcement rib that delivers greater rigidity.
- The sides have marks to facilitate the positioning of the bushing for joining boxes.
- The top and bottom sides have knock-outs with the standard metric diameters so that they can be quickly removed with a screwdriver for cable and pipe entry. These knockouts have central pre-marks to open other required diameters.
- The bottom of the base is fitted with supports for attaching neutral and earth bars, as well as the housings for attaching the DIN rail. It also has pre-marks to open other diameters.

#### **Frame**

- The frame has double height which gives it greater rigidity.
- The frame-base unit is closed by means of 1/4 turn captive sealable power screws. This creates a box that can be sealed at four points.
- Covered with a sealing gasket that guarantees the IP protection of the unit.

#### Window

- Transparent tinted windows with UV protection.
- The window is covered with a sealing gasket to guarantee the assembly's IP protection.
- Reversible 180° horizontal window opening, except CDN4G box with 90° vertical opening.
- Lock with the IDE logotype with pressure-operated opening and closing, except CDN4G. The lock can be replaced with key locks or triangular locks (inserts supplied as accessories).







#### **DIN** rail attachment

- For 1-row models, the rail is inserted into the side housing, without a screw, and is secured by means of a screw on the other side.
- For models with 2 or more rows, a detachable frame is inserted.
- Double rail and frame positioning height as of 12 modules of capacity.
- The DIN rail is attached to the base with 4x13 special screws for plastic.
- The rails are supplied assembled in the bases.

#### Wall-mounting

- There are two possible wall-mounting systems:
- By means of four screws, directly from the housings located at the bottom of the base provided for this purpose; these housings are covered with hermetic caps (supplied in the accessories bag, ref. 77650) to maintain the degree of protection and dielectric strength.
- Through the holes made for the purpose of securing the frame-base, by means of four screws, except CDN4G.

## **ECOLOGY**

#### **IP65** distribution boxes

#### IP65 surface distribution boxes (ABS)

Reference No.	No. of modules Dimensions				Weight	Power		n accordin rease °C P		rature	RATE PER / NO
		HEIGHT	WIDTH	DEPTH	kg	20	25	30	35	40	
CDN4G	1x4 DIN rail	177	102	105	0.3	5.0	6.2	7.5	8.7	10.0	2500
CDN4PT	1x4 DIN rail	231	166	113	0.7	8.9	11.1	13.3	15.5	17.8	3000
CDN6PT	1x6 DIN rail	231	202	113	0.9	10.1	12.6	15.1	17.7	20.2	3500
CDN8PT	1x8 DIN rail	231	238	118	1.0	11.6	14.5	17.4	20.3	23.1	4000
CDN12PT	1x12 DIN rail	246	310	148	1.4	16.6	20.7	24.8	29.0	33.1	5400
CDN18PT	1x18 DIN rail	286	418	148	2.0	23.1	28.9	34.7	40.4	46.2	7300

CONTINUED ON PAGE 266.

#### IP65 surface distribution boxes (Polycarbonate)

Reference No.	No. of modules	D	imensio	ns	Weight	Power		n accordin rease °C P		rature	RATE PER / NO
		HEIGHT	WIDTH	DEPTH	kg	20	25	30	35	40	
CDP4PT	1x4 DIN rail	231	166	113	0.8	8.9	11.1	13.3	15.5	17.8	3500
CDP6PT	1x6 DIN rail	231	202	113	1.0	10.1	12.6	15.1	17.7	20.2	4000
CDP8PT	1x8 DIN rail	231	238	118	1.0	11.6	14.5	17.4	20.3	23.1	5000
CDP12PT	1x12 DIN rail	246	310	148	1.5	16.6	20.7	24.8	29.0	33.1	6400
CDP18PT	1x18 DIN rail	286	418	148	2.1	23.1	28.9	34.7	40.4	46.2	8500

#### **CONTINUED ON PAGE 266.**

#### HALOGEN-FREE PLASTIC MATERIALS, WITH UV PROTECTION

Ref. CDN: Frame and base in ABS RAL 7035 grey. Transparent PC tinted window. Ref. CDP: Frame and base in PC RAL 7035 grey. Transparent PC tinted window. IP65 - Surface - Sealable.



## 1x4 modules CDN4G

TOP: 1xM25




## 1x4 modules CDN4PT


TOP: 2xM25-1xM40 BOTTOM: 2xM25-1xM40 OBLONG REAR: 2xOB25/25




## 1x6 modules CDN6PT

TOP: 2xM25-1xM40 BOTTOM: 2xM25-1xM40 OBLONG REAR: 2xOB25/25













#### IP65 surface distribution boxes. With neutral and earth bars (ABS)

Reference No.	No. of modules	of modules Dimensions				Power		n accordin rease °C P		rature	RATE PER / NO
		HEIGHT	WIDTH	DEPTH	kg	20	25	30	35	40	
CDN4G/R	1x4 DIN rail	177	102	105	0.5	5.0	6.2	7.5	8.7	10.0	2800
CDN4PT/RR	1x4 DIN rail	231	166	113	0.8	8.9	11.1	13.3	15.5	17.8	3300
CDN6PT/RR	1x6 DIN rail	231	202	113	1.0	10.1	12.6	15.1	17.7	20.2	3800
CDN8PT/RR	1x8 DIN rail	231	238	118	1.1	11.6	14.5	17.4	20.3	23.1	4300
CDN12PT/RR	1x12 DIN rail	246	310	148	1.6	16.6	20.7	24.8	29.0	33.1	6000
CDN18PT/RR	1x18 DIN rail	286	418	148	2.2	23.1	28.9	34.7	40.4	46.2	7600

CONTINUED ON PAGE 267.

#### IP65 surface distribution boxes. With neutral and earth bars (Polycarbonate)

Reference No.	No. of modules	D	imensio	ns	Weight	Power		n accordin rease °C P		rature	RATE PER / NO
		HEIGHT	WIDTH	DEPTH	kg	20	25	30	35	40	
CDP4PT/RR	1x4 DIN rail	231	166	113	0.9	8.9	11.1	13.3	15.5	17.8	3800
CDP6PT/RR	1x6 DIN rail	231	202	113	1.0	10.1	12.6	15.1	17.7	20.2	4300
CDP8PT/RR	1x8 DIN rail	231	238	118	1.1	11.6	14.5	17.4	20.3	23.1	5300
CDP12PT/RR	1x12 DIN rail	246	310	148	1.7	16.6	20.7	24.8	29.0	33.1	6700
CDP18PT/RR	1x18 DIN rail	286	418	148	2.3	23.1	28.9	34.7	40.4	46.2	8800

#### **CONTINUED ON PAGE 267.**

#### HALOGEN-FREE PLASTIC MATERIALS, WITH UV PROTECTION

Ref. CDN: Frame and base in ABS RAL 7035 grey. Transparent PC tinted window. Ref. CDP: Frame and base in PC RAL 7035 grey. Transparent PC tinted window.


IP65 - Surface - Sealable.

/RR: With neutral and earth bars. /R: With busbar PE or neutral.



## 1x8 modules CDN8PT


TOP: 4xM25-1xM40 BOTTOM: 4xM25+1xM40 INT: -OBLONG REAR: 2xOB25/25





## 1x12 modules CDN12PT


TOP: 6xM20-2xM25-2xM32-1xM40 BOTTOM: 6xM20-2xM25-2xM32-1xM40 INT: 4xM25 OBLONG REAR: 2xOB 25/32/25





#### 1x18 modules CDN18PT

TOP: 12xM20-6xM25-2xM32-1xM40 BOTTOM: 12xM20-6xM25-2xM32-1xM40 INT: 4xM25 OBLONG REAR: 2xOB 25/32/25



## **ECOLOGY**

#### **IP65** distribution boxes

#### IP65 surface distribution boxes (ABS)

Reference No.	No. of modules	D	imensio	ns	Weight	Power	Power dissipation according to temperature increase °C P(W)						
		HEIGHT	WIDTH	DEPTH	kg	20	25	30	35	40			
CDN24PT	2x12 (24) DIN rail	436	310	148	2.4	25.9	32.3	38.8	45.3	51.7	9700		
CDN36PT2F	2x18 (36) DIN rail	436	418	148	3.1	32.1	40.1	48.1	56.1	64.1	11700		
CDN36PT3F	3x12 (36) DIN rail	586	310	148	3.1	33.2	41.5	49.8	58.1	66.5	13000		
CDN54PT	3x18 (54) DIN rail	586	418	148	4.0	41.0	51.2	61.5	71.7	82.0	18700		

#### IP65 surface distribution boxes (Polycarbonate)

Reference No.	No. of modules	D	imensio	ns	Weight	Power		n accordin rease °C P	-	rature	RATE PER / NO
		HEIGHT	WIDTH	DEPTH	kg	20	25	30	35	40	
CDP24PT	2x12 (24) DIN rail	436	310	148	2.6	25.9	32.3	38.8	45.3	51.7	11000
CDP36PT2F	2x18 (36) DIN rail	436	418	148	3.3	32.1	40.1	48.1	56.1	64.1	13000
CDP36PT3F	3x12 (36) DIN rail	586	310	148	3.3	33.2	41.5	49.8	58.1	66.5	14000
CDP54PT	3x18 (54) DIN rail	586	418	148	4.3	41.0	51.2	61.5	71.7	82.0	20000


#### HALOGEN-FREE PLASTIC MATERIALS, WITH UV PROTECTION

Ref. CDN: Frame and base in ABS RAL 7035 grey. Transparent PC tinted window. Ref. CDP: Frame and base in PC RAL 7035 grey. Transparent PC tinted window. IP65 - Surface - Sealable.



#### 2x12 (24) modules CDN24PT


TOP: 8xM20-2xM25-2xM32-1xM40 BOTTOM: 6xM20-2xM25-2xM32-1xM40 INT: 4xM25 OBLONG REAR: 2xOB 25/32/25



## 2x18 (36) modules CDN36PT2F


TOP: 12xM20-6xM25-2xM32-1xM40 BOTTOM: 12xM20-6xM25-2xM32-1xM40 INT: 4xM25

OBLONG REAR: 2xOB 25/32/25




## 3x12 (36) modules CDN36PT3F

TOP: 8xM20-2xM25-2xM32-1xM40 BOTTOM: 6xM20-2xM25-2xM32-1xM40 INT: 4xM25 OBLONG REAR: 2xOB 25/32/25



## 3x18 (54) modules CDN54PT

TOP: 12xM20-6xM25-2xM32-1xM40 BOTTOM: 12xM20- 6xM25-2xM32-1xM40 INT: 4xM25 OBLONG REAR: 2xOB 25/32/25









#### IP65 surface distribution boxes. With neutral and earth bars (ABS)

Reference No.	No. of modules	D	Dimensions		Weight	Power dissipation according to temperature increase °C P(W)					RATE PER / NO
		HEIGHT	WIDTH	DEPTH	kg	20	25	30	35	40	
CDN24PT/RR	2x12 (24) DIN rail	436	310	148	2.6	25.9	32.3	38.8	45.3	51.7	10000
CDN36PT2F/RR	2x18 (36) DIN rail	436	418	148	3.4	32.1	40.1	48.1	56.1	64.1	12000
CDN36PT3F/RR	3x12 (36) DIN rail	586	310	148	3.4	33.2	41.5	49.8	58.1	66.5	13500
CDN54PT/RR	3x18 (54) DIN rail	. 586	418	148	4.4	41.0	51.2	61.5	71.7	82.0	19000

#### IP65 surface distribution boxes. With neutral and earth bars (Polycarbonate)

Reference No.	No. of modules	D	Dimensions		Weight	Power dissipation according to temperature increase °C P(W)					RATE PER / NO
		HEIGHT	WIDTH	DEPTH	kg	20	25	30	35	40	
CDP24PT/RR	2x12 (24) DIN rail	436	310	148	2.8	25.9	32.3	38.8	45.3	51.7	12500
CDP36PT2F/RR	2x18 (36) DIN rail	436	418	148	3.6	32.1	40.1	48.1	56.1	64.1	13500
CDP36PT3F/RR	3x12 (36) DIN rail	. 586	310	148	3.6	33.2	41.5	49.8	58.1	66.5	14500
CDP54PT/RR	3x18 (54) DIN rail	. 586	418	148	4.7	41.0	51.2	61.5	71.7	82.0	20500

#### HALOGEN-FREE PLASTIC MATERIALS, WITH UV PROTECTION

Ref. CDN: Frame and base in ABS RAL 7035 grey. Transparent PC tinted window.

Ref. CDP: Frame and base in PC RAL 7035 grey. Transparent PC tinted window.

IP65 - Surface - Sealable.

/RR: With neutral and earth bars.

# Ultra-modern design and plenty of space for wiring

## **ECO-STAR SYSTEM**

#### Ecology Series (Distribution boxes) + Star Series (Boxes for industrial sockets)

The Eco-Star system gives the possibility of joining the IP65 watertight distribution boxes (Ecology series) and IP65 boxes for industrial sockets (Star series), to create large-sized assemblies and modular capacity.

Combined with each other, they offer the installer the most versatile internationally-certified solution to combine distribution boxes and units for power sockets.

They have ample room for cables and extensive modular capacity. Intented for indoor and outdoor uses, wherever a high degree of protection and safety is required.





REF. 94273: M25 BUSHING

REF. 94274: M40 BUSHING

## Join system

Joining these two models makes it possible to create large-sized power supply and distribution enclosures.

The boxes have marks on the sides for the easy installation of M25 and M40 bushings with rubber gasket to guarantee IP65 protection. They can be joined both vertically and horizontally.

The use of two M25 cable glands or a combination of an M25 cable gland and an M40 cable gland is recommended when more space is needed to run the cables.

## Different joining possibilities and combinations



CDN24PT+CSN12PT

CSN12PT+PCSNPLUS

PCSN12PT+PCSN6PT



#### **STAR + Additional module**



D ( )	N		Compo	onents	
Reference No.	No. of modules	Weight	References		
		kg			
CSN12PT/PLUS	1x12 DIN rail + Additional	3.0	CSN12PT	CSNPLUS	
0311121 1/1 203	TXTZ BITT Tale : Additional	0.0	03111211	03111 203	

#### HALOGEN-FREE PLASTIC MATERIALS

FINISH: Grey RAL 7035 with transparent window.

**DIMENSIONS:** 436x452x147 mm.

IP65 - Surface.



Reference No.	No. of modules	Waimbt	Components			
Reference No.	rence No. No. of modules Weight		References			
		kg				
CSN18PT/PLUS	1x18 DIN rail + Additional	3.6	CSN18PT	CSNPLUS		

#### HALOGEN-FREE PLASTIC MATERIALS

FINISH: Grey RAL 7035 with transparent window.

**DIMENSIONS:** 436x560x147 mm.

IP65 - Surface.



Deference No	No of modulos	\A/a:= a	Components			
Reference No.	No. of modules	modules Weight Ro		ences	No. of lids	
		kg				
PCSN12PT/PLUS	1x12 DIN rail + Additional	3 3	PCSN12PT	PCSNPLUS	15	

#### HALOGEN-FREE PLASTIC MATERIALS

FINISH: Grey RAL 7035 with transparent window.

**DIMENSIONS:** 436x452x147 mm.

IP65 - Surface.



Deference No	No of modulos	\A/=:=b4	Components			
Reference No.	No. of modules	Weight	Refer	No. of lids		
		kg				
PCSN18PT/PLUS	1x18 DIN rail + Additional	4.0	PCSN18PT	PCSNPLUS	20	

#### HALOGEN-FREE PLASTIC MATERIALS

FINISH: Grey RAL 7035 with transparent window.

**DIMENSIONS:** 436x560x147 mm.

IP65 - Surface.

#### ECOLOGY + Additional module



Defense No	No. of mondator	\A/a:la4	Components			
Reference No.	No. of modules	Weight	References		No. of lids	
		kg				
CDN24PT/PLUS	2x12 (24) DIN rail + Additional	3.5	CDN24PT	PCSNPLUS	5	

#### HALOGEN-FREE PLASTIC MATERIALS

FINISH: Grey RAL 7035 with transparent window.

**DIMENSIONS:** 436x452x147 mm.

IP65 - Surface.



Deference No	No informations	\A/-:	Components			
Reference No.	No. of modules	Weight	References	No. of lids		
		kg				
CDN36PT2F/PLUS	2x18 (36) DIN rail + Additional	4.2	CDN36PT2F PCSNPLUS	S 5		

#### HALOGEN-FREE PLASTIC MATERIALS

FINISH: Grey RAL 7035 with transparent window.

**DIMENSIONS:** 436x560x147 mm.

IP65 - Surface.

# STAR IP65 Boxes for industrial sockets

The STAR series comprises a set of enclosures for surface installation manufactured with halogen-free high-durability plastic materials. They are intended for housing power sockets or control and signalling elements. They are intended for installation in places requiring power points for fixed machinery, portable tools or auxiliary electrical equipment. Their sphere of application therefore includes industrial premises, workshops, warehouses, depot areas, building sites, etc.. or any place requiring a high degree of protection and safety.

Their design allows them to be installed jointly with junction boxes of the Ecology series in order to create large-sized power and distribution panels intended for indoor and outdoor settings. provided that the components fulfil the applicable legislation.







#### **STAR Technical Specifications**

- Degree of protection: IP65.

- Resistance to impact: IK08. - Glow wire resistance: 650 °C.

- Ambient temperature range: -25 °C / +40 °C. - Maximum operating voltage: 1000 V AC/1500 V DC.

- Double insulation: Class II.

#### **STAR Certifications**

Compliant with the Low Voltage Directive 2014/35/EU. Standards: UNE-EN 62208 and UNE-EN 61439-1 (as applicable).

## **STAR**

#### IP65 boxes for industrial sockets



#### **Product series**

- Surface enclosures with a capacity of 4, 6, 9, 12, 18, 24 and 36 modules with transparent window.
- Interface box to provide greater capacity.

#### **Material**

- Halogen-free plastic materials, with UV protection.
- Enclosure: ABS RAL 7035.
- Transparent window: PC tinted window.

#### Supply

- Supplied in individual cardboard packaging. When several items are sent together, they are bundled together with transparent film.
- The enclosure is supplied with the windows assembled on the cover and the hinges attached to the base, leaving the cover totally free for handling by the installer. The rails are supplied assembled in all references.
- Accessory bag:
  - Base/cover screws.
  - Grey module cover (6 modules).
  - Module identification strips.
  - Hermetic caps.
  - Cover-base hinges.
  - Assembly instructions.

# Enclosures for surface installation, intended for housing power sockets or control and signalling elements

#### Neutral and earth bars

In some markets, the technical regulations governing installation require neutral and earth conductors to be connected to a common busbar. The base of these boxes has specific supports for this purpose. The neutral and earth bars will be screwed to these supports, which are supplied as an accessory.

They can be supplied pre-assembled by ordering the /RR references.

#### Neutral and earth bar structure

Ref. No.	Tern	ninal	Cable s	ection
	Ν	Е	NEUTRAL	EARTH
22019	5+1	-	1x(16-35 mm²)+5x(10-25 mm²)	-
22007	4+2	4+2	$4x(2,5-6 \text{ mm}^2)+2x(4-10 \text{ mm}^2)$	$4x(2,5-6 \text{ mm}^2)+2x(4-10 \text{ mm}^2)$
22001	8+1	8+1	5x(2,5-6 mm²)+3x(4-10 mm²)+1x(16-35 mm²)	5x(2,5-6 mm²)+3x(4-10 mm²)+1x(16-35 mm²)
22002	12+2	12+2	$6x(2,5-6 \text{ mm}^2)+6x(4-10 \text{ mm}^2)+1x(10-25 \text{ mm}^2)+1x(16-35 \text{ mm}^2)$	6x(2,5-6 mm²)+6x(4-10 mm²)+1x(10-25 mm²)+1x(16-35 mm²)
22003	16+2	16+2	$8x(2,5-6 \text{ mm}^2)+8x(4-10 \text{ mm}^2)+1x(10-25 \text{ mm}^2)+1x(16-35 \text{ mm}^2)$	8x(2,5-6 mm²)+8x(4-10 mm²)+1x(10-25 mm²)+1x(16-35 mm²)
22004	24+2	24+2	12x(2,5-6 mm²)+12x(4-10 mm²)+1x(10-25 mm²)+1x(16-35 mm²)	12x(2,5-6 mm²)+12x(4-10 mm²)+1x(10-25 mm²)+1x(16-35 mm²)
















#### Base

- Base with double height DIN rail (from 12 modules) providing greater space on the inside for wiring and devices, and a reinforcement rib that delivers greater rigidity.
- The sides have marks to facilitate the positioning of the bushing for joining boxes.
- The top and bottom sides have knock-outs with the standard metric diameters so that they can be quickly removed with a screwdriver for cable and pipe entry. These knockouts have central pre-marks to open other required diameters.
- The bottom of the base is fitted with supports for attaching neutral and earth bars, as well as the housings for attaching the DIN rail. It also has pre-marks to open other diameters.

#### **DIN** rail attachment

 The rail is clipped and screwed to the base. The rails are supplied assembled in the base.

#### Wall-mounting

- Wall-mounting is by means of four screws, directly from the housings located at the bottom of the base provided for this purpose. These housings are covered with hermetic caps (supplied in the accessories bag, ref. 77650) to maintain the degree of protection and dielectric strength.

#### **Frame**

- The frame is used for placing the power sockets and has a blank vertical area. Frame size varies depending on sizes, and all types of sockets can be fitted.
- The frame perimeter and the front of the box have protection from dust and water. The front side includes a sealing gasket on the window that guarantees the IP protection from dust and water.
- The geometry of the frame and its constituent elements give the part greater rigidity. The frame-base unit is closed by means of captive screws (supplied in the accessory bag).









#### Window

- Transparent tinted windows, with UV protection.
- The window has reinforcement ribs to provide rigidity and pressure on the sealing gasket of the frame that guarantees IP protection of the assembly.
- Handle with vertical opening in 4, 6 and 9-modules models, and  $180^{\circ}$  reversible horizontal window opening in 12, 18, 24 and 36-module models.
- Lock with the IDE logotype with pressure-operated opening and closing, except CSN4PT.
- The lock can be replaced with key locks or triangular locks (inserts supplied as accessories).

#### Frame-base hinge system


- This series has a frame-base hinge system that enhances manoeuvrability between both parts, guaranteeing both vertical and horizontal opening of 180°, except CSN4PT.
- The hinges' high resistance means that when the base is secured to the wall, the frame can be left hanging even if it has been totally installed with sockets or with equipment.
- The unit is assembled and disassembled by gently pressing on the ends of the part, which is symmetrical and reversible.

#### IP65 boxes for industrial sockets

#### IP65 boxes for industrial sockets

Reference No.	No. of modules	Dimensions			Weight	Power dissipation according to temperature increase °C P(W)					RATE PER / NO
		HEIGHT	WIDTH	DEPTH	kg	20	25	30	35	40	
CSNPLUS	-	436	142	124	0.9	14.6	18.3	21.9	25.6	29.2	3500
CSN4PT	1x4 DIN rail	385	102	105	0.6	10.0	12.5	15.0	17.5	20.0	3800
CSN6PT	1x6 DIN rail	436	142	137	1.1	15.5	19.4	23.3	27.1	31.0	6000
CSN9PT	1x9 DIN rail	436	210	137	1.4	19.3	24.1	29.0	33.8	38.6	8000
CSN12PT	1x12 DIN rail	436	310	147	2.0	25.8	32.2	38.7	45.1	51.6	9800
CSN18PT	1x18 DIN rail	436	418	147	2.5	32.0	39.9	47.9	55.9	63.9	12000
CSN24PT	2x12 (24) DIN rail	688	310	147	3.5	37.1	46.4	55.7	65.0	74.3	14500
CSN36PT	2x18 (36) DIN rail	728	418	147	4.6	49.5	61.8	74.2	86.6	98.9	16500

Frame and base in ABS RAL 7035 grey. PC transparent window, tinted. IP65 - Surface.



TOP: 2xM20 - 1xM40 BOTTOM: 2xM20 - 1xM40 REAR OBLONG:2xOB25x25

**CSNPLUS** 



## 1x4 modules CSN4PT

REAR: 2xM20



1x6 modules CSN6PT

TOP: 2xM20 - 1xM40 BOTTOM: 2xM20 - 1xM40 REAR OBLONG:2xOB25x25




## 1x9 modules CSN9PT


TOP: 4xM20 - 1xM40 BOTTOM: 4xM20 - 1xM40 REAR OBLONG:2x0B25x25





## 1x12 modules CSN12PT

TOP: 8xM20-2xM25/32-1xM40 BOTTOM: 4xM20-2xM25-2xM32-1xM40 REAR OBLONG: 2xOB 25/32/25















#### IP65 boxes for industrial sockets. With neutral and earth bars

Reference No.	No. of modules	D	imensio	ns	Weight	Powe	r dissipatio inc	n accordin rease °C P		rature	RATE PER / NO
		HEIGHT	WIDTH	DEPTH	kg	20	25	30	35	40	
CSNPLUS/RR	-	436	142	124	1.0	10.5	13.2	15.8	18.4	21.0	4000
CSN4PT/R	1x4 DIN rail	385	102	105	0.7	10.0	12.5	15.0	17.5	20.0	4300
CSN6PT/RR	1x6 DIN rail	436	142	137	1.2	14.3	17.9	21.5	25.1	28.7	7500
CSN9PT/RR	1x9 DIN rail	436	210	137	1.5	16.7	20.9	25.1	29.2	33.4	8500
CSN12PT/RR	1x12 DIN rail	436	310	147	2.2	24.1	30.1	36.1	42.1	48.2	11000
CSN18PT/RR	1x18 DIN rail	436	418	147	2.7	30.0	37.5	45.1	52.6	60.1	13500
CSN24PT/RR	2x12 (24) DIN rail	688	310	147	3.8	30.4	38.0	45.7	53.3	60.9	15500
CSN36PT/RR	2x18 (36) DIN rail	728	418	147	4.9	49.5	61.8	74.2	86.6	98.8	17500

#### HALOGEN-FREE PLASTIC MATERIALS, WITH UV PROTECTION

Frame and base in ABS RAL 7035 grey.

Transparent PC tinted window.

IP65 - Surface.


/RR: With neutral and earth bars.

/R: With busbar PE or neutral.



#### 1x18 modules CSN18PT


TOP: 12xM20-6xM25-2xM32-1xM40 BOTTOM: 10xM20-6xM25-2xM32-1xM40 REAR OBLONG: 2xOB 25/32/25





## 2x12 (24) modules CSN24PT


TOP: 6xM20-2xM25-2xM32-1xM40 BOTTOM: 4xM20-2xM25-1xM40 REAR OBLONG: 4xOB 25/32/25





## 2x18 (36) modules CSN36PT

TOP: 1xM40-2xM32-6xM25-12xM20 BOTTOM: 1xM40-2xM32-6xM25-10xM20 REAR OBLONG: 4xOB25/32/25



## STAR KNOCK-OUT

#### IP65 boxes for industrial sockets with knock-out lids



#### **Product series**

- Surface enclosures with a capacity 6, 9, 12, 18, 24 and 36 modules with transparent window.
- Wall-mounted enclosures with knock-out and interchangeable covers, to install different types of sockets with multiple combinations.
- Interface box available to provide greater capacity.

#### Material

- Halogen-free plastic materials, with UV protection.
- Base: ABS RAL 7035.
- Transparent window: PC tinted window.

#### Supply

- Supplied in individual cardboard packaging. When several items are sent together, they are bundled together with transparent film.
- The enclosure is supplied with the windows assembled on the cover and the hinges attached to the base, leaving the cover totally free for handling by the installer. The rails are supplied assembled in all references.
- Accessory bag:
  - Base/cover screws.
  - Grey module cover (6 modules).
  - Module identification strips.
  - Hermetic caps.
  - Cover-base hinges.
  - Assembly instructions.

## Watertight boxes for installation of industrial sockets

#### Interchangeable covers

The enclosure is supplied with the interchangeable covers as below:

Reference No.	Plain covers	16A/ IP67 Schuko-type covers	IP44/IP54 Schuko-type covers
	Ref. 94270	Ref. 94271	Ref. 94272
PCSNPLUS	3	1	1
PCSN6PT	2	1	1
PCSN9PT	4	2	2
PCSN12PT	6	2	2
PCSN18PT	8	3	4
PCSN24PT	6	2	2
PCSN36PT	8	3	4



#### **Knock-out lids**

Reference No.	Description	Bases	Current (A)	Poles	IP
	Districtions Cumplied assembled	Flush-fit	16	3P+N+E	IP44 - IP67
	Plain covers: Supplied assembled. Remove the cover in order to install sockets.	Flush-fit	32	2P+E - 3P+E - 3P+N+E	IP44 - IP67
0/071	16 A cover: Supplied in the box.	Flush-fit	16	2P+E - 3P+E	IP44 - IP67
	Screw-in cover for socket installation.	Schuko-type	16	2P+E	IP67
94272	Schuko-type cover: Supplied in the box. Screw-in and clip-on cover for Schuko-type socket installation.	Schuko-type	16	2P+E	IP44 - IP54

#### **Possibility of lids**







It is supplied assembled, with knockouts for the installation of pilot lights or pushbuttons.

Remove the plain cover in order to install sockets.

- 16 A (3P+N+E) IP44-IP67.
- 32 A IP44-IP67.



#### 2. 16A COVER (Ref. 94271)

Screw-in cover for socket installation:

- 16 A (2P+E) (3P+E) IP44-IP67.
- Schuko-type 16 A IP67.



#### 3. SCHUKO-TYPE COVER (Ref. 94272)

Screw-in and clip-on cover for Schuko-type 16 A sockets - IP44-IP54.

## STAR KNOCK-OUT

#### IP65 boxes for industrial sockets with knock-out lids

#### IP65 boxes for industrial sockets. With knock-out lids

Reference No.	No. of modules	D	imensio	ns	No. of covers	Weight	Power		n accordin rease °C P		rature	Туре
		HEIGHT	WIDTH	DEPTH		kg	20	25	30	35	40	
PCSNPLUS	-	436	142	124	5	1.1	14.6	18.3	21.9	25.6	29.2	65TC00TR
PCSN6PT	1x6 DIN rail	436	142	137	4	1.2	15.5	19.4	23.3	27.1	31.0	65TC06TR
PCSN9PT	1x9 DIN rail	436	210	137	8	1.6	19.3	24.1	29.0	33.8	38.6	65TC09TR
PCSN12PT	1x12 DIN rail	436	310	147	10	2.2	25.8	32.2	38.7	45.1	51.6	65TC12TR
PCSN18PT	1x18 DIN rail	436	418	147	15	2.8	32.0	39.9	47.9	55.9	63.9	65TC18TR
PCSN24PT	2x12 (24) DIN rail	688	310	147	10	3.8	37.1	46.4	55.7	65.0	74.3	65TC24TR
PCSN36PT	2x18 (36) DIN rail	728	418	147	15	4.9	49.5	61.8	74.2	86.6	98.9	65TC36TR

#### HALOGEN-FREE PLASTIC MATERIALS, WITH UV PROTECTION

Frame and base in ABS RAL 7035 grey.

Transparent PC tinted window.

IP65 - Surface.



#### **PCSNPLUS**

TOP: 2xM20 - 1xM40 BOTTOM: 2xM20 - 1xM40 OBLONG REAR: 2xOB25x25

## 1x6 modules PCSN6PT


TOP: 2xM20 - 1xM40 BOTTOM: 2xM20 - 1xM40 OBLONG REAR:2xOB25x25


## 1x9 modules PCSN9PT


TOP: 4xM20 - 1xM40 BOTTOM: 4xM20 - 1xM40 OBLONG REAR: 2xOB25x25


## 1x12 modules PCSN12PT

TOP: 8xM20-2xM25/32-1xM40 BOTTOM: 4xM20-2xM25-2xM32-1xM40 OBLONG REAR: 2xOB 25/32/25









IP 65



#### IP65 boxes for industrial sockets. With knock-out lids. With neutral and earth bars

Reference No.	No. of modules	Dimensions		No. of covers	Weight	Power dissipation according to temperature increase °C P(W)			rature	Type		
						kg	20	25	30	35	40	
PCSNPLUS/RR	-	436	142	124	5	1.1	14.6	18.3	21.9	25.6	29.2	65TC00TR
PCSN6PT/RR	1x6 DIN rail	436	142	137	4	1.3	15.5	19.4	23.3	27.1	31.0	65TC06TR
PCSN9PT/RR	1x9 DIN rail	436	210	137	8	1.7	19.3	24.1	29.0	33.8	38.6	65TC09TR
PCSN12PT/RR	1x12 DIN rail	436	310	147	10	2.4	25.8	32.2	38.7	45.1	51.6	65TC12TR
PCSN18PT/RR	1x18 DIN rail	436	418	147	15	3.0	32.0	39.9	47.9	55.9	63.9	65TC18TR
PCSN24PT/RR	2x12 (24) DIN rail	688	310	147	10	4.0	37.1	46.4	55.7	65.0	74.3	65TC24TR
PCSN36PT/RR	2x18 (36) DIN rail	728	418	147	15	5.2	49.5	61.8	74.2	86.6	98.9	65TC36TR

#### HALOGEN-FREE PLASTIC MATERIALS, WITH UV PROTECTION

Frame and base in ABS RAL 7035 grey.

Transparent PC tinted window.


IP65 - Surface.

/RR: With neutral and earth bars.



## 1x18 modules PCSN18PT


TOP: 12xM20-6xM25/32-1xM40 BOTTOM: 10xM20-6xM25-2xM32-1xM40 OBLONG REAR: 2xOB 25/32/25





## 2x12 (24) modules PCSN24PT


TOP: 6xM20-2xM25-2xM32-1xM40 BOTTOM: 4xM20-2xM25-2xM32-1xM40 OBLONG REAR: 4xOB 25/32/25





## 2x18 (36) modules PCSN36PT

TOP: 1xM40-2xM32-6xM25-12xM20 BOTTOM: 1xM40-2xM32-6xM25-10xM20 OBLONG REAR: 4xOB25/32/25




## **STAR**

#### IP65 boxes for industrial sockets

#### Special assemblies

4 DIFFERENT POSSIBILITIES.





#### How to proceed



1. SELECT THE BOX.



2. CHOOSE THE POWER SOCKETS.



3. INDICATE THE REQUIRED PROTECTION.



4. SUBMIT ALL THE INFORMATION TO OUR TECHNICAL DEPARTMENT.

You can request a quotation and technical assessment at export@ide.es

Special assemblies can be supplied in any combination, assembled and wired, with no minimum order quantity

#### Proposal of sockets for Star boxes

SCHUKO-TYPE FLUSH-FIT SOCKETS

IP44 FLUSH-FIT SOCKETS

**IP67 FLUSH-FIT SOCKETS** 

REF.	Poles	1	IP
00102	2P+E	16 A	44
00452	2P+E	16 A	54
00105	2P+E	16 A	67

REF.	Poles	1	Voltage
02301	2P+E	16 A	200/250 V
03302	3P+E	16 A	380/415 V
03303	3P+N+E	16 A	200/415 V
02304	2P+E	32 A	200/250 V
03305	3P+E	32 A	380/415 V
03306	3P+N+E	32 A	200/415 V

REF.	Poles	1	Voltage
02801	2P+E	16 A	200/250 V
03802	3P+E	16 A	380/415 V
03803	3P+N+E	16 A	200/415 V
02804	2P+E	32 A	200/250 V
03805	3P+E	32 A	380/415 V
03806	3P+N+E	32 A	200/415 V

See our full range of plugs and sockets on Mundial series

# PRYMA IP67 Boxes for industrial sockets

The PRYMA series comprises a set of enclosures for surface installation, manufactured with halogen-free high-durability plastic materials intended to house power sockets or control and signalling elements.

They are intended for installation in places requiring power points for fixed machinery, portable tools or auxiliary electrical equipment.

Their sphere of application therefore includes industrial premises, workshops, warehouses, depot areas, building sites, etc., or any place requiring a high degree of protection and safety.





#### **PRYMA Technical Specifications**

- Degree of protection: IP67.

- Resistance to impact: IK08.

- Glow wire resistance: 650 °C.

- Ambient temperature range: -25  $^{\circ}\text{C}$  / +40  $^{\circ}\text{C}$  .

- Maximum operating voltage: 1000 V AC/1500 V DC.

- Double insulation: Class II.

#### **PRYMA Certifications**

Compliant with the Low Voltage Directive 2014/35/EU. Standards: UNE-EN 62208 and UNE-EN 61439-1 (as applicable).

### **PRYMA**

#### IP67 boxes for industrial sockets



#### **Product series**

- Surface enclosures with a capacity of 9, 13 and 26 modules with transparent window.

#### **Material**

- Halogen-free plastic materials, with UV protection.
- Base and frame: ABS RAL 7035.
- Transparent window: PC tinted window.

#### Supply

- Supplied in individual cardboard packaging. When several items are sent together, they are bundled together with transparent film.
- The enclosure is supplied with the windows assembled on the cover and the hinges attached to the base, leaving the cover totally free for handling by the installer.
- The rails are supplied assembled to the base for the 9-module models. For the 13- and 26-module models they are supplied disassembled in a bag containing the rail, supports and screws.
- Accessory bag:
  - 11x13 plastic screws.
  - Grey module cover (6 modules).
  - Module identification strips.
  - Hermetic caps (Ref. No. 1712GM and 1724GM).
  - Assembly instructions.

## Intended for the industrial sector, where a high degree of safety and maximum protection are required

#### **DIN** rail attachment

- The rail can be attached to the enclosure in two different positions: to the base or to the cover.

#### Attachment of rail to cover:

 - 178M, 178P, 1712GM and 1724GM boxes: two supports are screwed to the cover, and the DIN rail is then screwed onto the supports.

#### Attachment of rail to base:

- 178M and 178P boxes: by pressing the rail gently into two grooved housings. These boxes are supplied with the rail assembled on the base.

- 1712GM and 1724GM boxes: two supports are screwed to the base and the DIN rail is then screwed onto the supports. The DIN rail can be placed at two different heights, offering the possibility of fitting elements from 53 mm to 70 mm for the first position and 92 mm for the second one. The boxes are supplied with the bag of accessories required for installation.

IP 67









#### Base

- It has four completely flat walls, permitting the installation of small elements such as pilot lights, pushbuttons, etc.
- The side walls have vertical ribs on the inside that provide rigidity to protect against possible deformation.
- The top and bottom sides are also flat, with three pre-marked points that can be used as a reference for inserting the trunking pipe.
- The bottom of the base is fitted with supports for attaching neutral and earth bars, as well as the housings for attaching the DIN rail.
- The base has raised lines with different housings for fixing mounting plates, rails, bars, etc.

#### Wall-mounting

- 178P and 178M boxes are secured to the wall by means of screws placed in the locking screw housings on the enclosure.
- 1712GM and 1724GM boxes are mounted directly from the housings located on the base for this purpose. These housings are covered with watertight caps (supplied in the accessories bag) to maintain the degree of protection and dielectric strength.

#### **Frame**

- The frame is used for placing the power sockets. It has a vertical blank area and another one with an inclined plane to facilitate base installation and to prevent cable bundles from crossing.
- The frame perimeter has a sealing gasket to guarantee protection from dust and water.
- The inside of the frame has reinforcement ribs to guarantee the part's rigidity.
- The frame-base assembly is closed by means of 11×23 plastic pan-head and flat-tip screws (supplied in the accessory bag).
- The boxes can be sealed at two points.









#### Window

- Transparent tinted windows with UV protection.
- The window presses against the sealing gasket to guarantee the assembly's IP protection.
- The window opens vertically and is closed by means of two threaded screws.
- Possibility of support with padlock supplied as an accessory (Ref. 77670).

#### Frame-base hinge system

- This series has a frame-base hinge system that enhances manoeuvrability between both parts, guaranteeing an opening of 180°.
- The hinges' high resistance means that when the base is secured to the wall, the frame can be left hanging even if it has been totally installed with sockets or with equipment.
- The unit is assembled and disassembled by gently pressing on the ends of the part, which is symmetrical and reversible.

#### IP67 boxes for industrial sockets

#### IP67 wall-mounted enclosures for power sockets

Reference No.	No. of modules	Dimensions	Power dissipation according to temperature increase °C P(W)*			RATE PER / NO		
		HEIGHT X WIDTH X DEPTH	20	25	30	35	40	
178P	1x9 DIN rail	284x222x122	13.2	16.5	19.8	23.1	26.4	6000
178M	1x9 DIN rail	369x222x130	16.9	21.1	25.4	29.6	33.8	6500
1712GM	1x13 DIN rail	504x297x177	31.1	38.8	46.6	54.4	62.1	9000
1724GM	2x13 (26) DIN rail	504x297x177	31 1	38 8	46 6	54 4	62 1	11000

#### HALOGEN-FREE PLASTIC MATERIALS, WITH UV PROTECTION

Frame and base in ABS RAL 7035 grey.

PC transparent window, tinted.

IP67 - Surface.



1x9 modules 178P


1x9 modules 178M


1x13 modules 1712GM

182 234 297 279 279

1724GM

204 222 204 222





<sup>\*</sup> Calculations obtained according to the CEI 890:1997 standard (including Corrigendum 1998). Method of temperature-rise assessment by extrapolation for partially type-tested assemblies (PTTA) of low-voltage switchgear and control gear.

#### IP67 wall-mounted enclosures for power sockets. With neutral and earth bars

Reference No.	No. of modules	Dimensions		Power dis temperatu	RATE PER / NO			
		HEIGHT X WIDTH X DEPTH	20	25	30	35	40	
178P/RR	1x9 DIN rail	284x222x122	13.2	16.5	19.8	23.1	26.4	6500
178M/RR	1x9 DIN rail	369x222x130	16.9	21.1	25.4	29.6	33.8	7000
1712GM/RR	1x13 DIN rail	504x297x177	31.1	38.8	46.6	54.4	62.1	9500
1724GM/RR	2x13 (26) DIN rail	504x297x177	31.1	38.8	46.6	54.4	62.1	11500

#### HALOGEN-FREE PLASTIC MATERIALS, WITH UV PROTECTION

Frame and base in ABS RAL 7035 grey.

PC transparent window, tinted.

IP67 - Surface.

/RR: With neutral and earth bars.

They are intended for places requiring power points for fixed machinery, portable tools or auxiliary electrical equipment

<sup>\*</sup> Calculations obtained according to the CEI 890:1997 standard (including Corrigendum 1998). Method of temperature-rise assessment by extrapolation for partially type-tested assemblies (PTTA) of low-voltage switchgear and control gear.

## PRYMA COMPLET

#### IP67 boxes for industrial sockets

#### Special assemblies



Plain boxes.



Boxes with assembled and wired power sockets.



Boxes with assembled and wired power sockets and protections.

#### How to proceed



1. SELECT THE BOX.



2. CHOOSE THE POWER SOCKETS.



3. INDICATE THE REQUIRED PROTECTION.



4. SUBMIT ALL THE INFORMATION TO OUR TECHNICAL DEPARTMENT.

You can request a quotation and technical assessment at export@ide.es


Special assemblies with power sockets can be supplied in any combination, assembled and wired, with no minimum order quantity

#### Proposal of sockets for Pryma Complet boxes

IP67 SCHUKO-TYPE FLUSH-FIT SOCKETS

IP67 FLUSH-FIT SOCKETS








	Poles	1	Voltage
			/
02801	2P+E	16 A	200/250 V
03802	3P+E	16 A	380/415 V
03803	3P+N+E	16 A	200/415 V
02804	2P+E	32 A	200/250 V
03805	3P+E	32 A	380/415 V
03806	3P+N+E	32 A	200/415 V

See our full range of plugs and sockets on Mundial series











43, Rashmi Growth Hub, Opp, Shreya Residency, Near odhav Ring Road Circle, Odhav, Ahmedabad-382415, Gujarat, INDIA.



business@makewelltech.com



www.makewelltech.com



